



America


CERTIFICATE

No. U8 06 09 13563 035

Holder of Certificate: Arnold & Richter Cine Technik GmbH & Co Betriebs KG

Pulvermühle
83071 Stephanskirchen
GERMANY

Certification Mark:



Product: Luminaires
(Daylight luminaires for professional use)

The product was voluntarily tested according to the relevant safety requirements and mentioned properties. It can be marked with the certification mark shown above. The certification mark must not be altered in any way. See also notes overleaf.

Test report no.: 028-70077970-000

Date, 2006-09-27

Page 1 of 2





America

CERTIFICATE

No. U8 06 09 13563 035

Model(s):

Type: ARRILUX 125 models: L1.733xx.0
 (based id.-no. L173375.0)
 Type: ARRILUX 200 (Pocket Par), models:
 L1.7079x.y (based id.-no. L1.70790.y)
 Type: ARRILUX 200 (Pocket Lite) models:
 L1.7082x.y (based id.-no. L1.70820.y)
 Type: ARRILUX 400 (Pocket Par), models:
 L1.7088x.0 (based id.-no. L1.70880.0)
 Type: ARRILUX 400 (Pocket Lite) models:
 L1.7089x.0 (based id.-no. L1.70890.0)

Remark:

(Where x can be any number based on id.-no added with a value between 0 and 5 and describes mostly the color of the housing. Only for ARRILUX 200: Where y can be "P" and describes a version with reduced protection rate IP20 or y can be "0" and describes the standard version with a protection rate IP23.)

Brand Name:

ARRI

Parameters:

Typ ARRILUX	125	200	400
Rated voltage:	80 V	70 V	70 V
Rated power:	125 W	200 W	400 W
Rated current:	1,6 A	3,0 A	6,9 A
Rated frequency:	50 to 100 Hz all types		
Protection class:	I	I	I
Degree of protection:	IP20:	ARRILUX 125, L1.733xx.0 and ARRILUX 200, L1.7079x.P and L1.7082x.P	
	IP23:	ARRILUX 200, L1.7079x.0 and L1.7082x.0 and ARRILUX 400, L1.7088x.0 and L1.7089x.0	

Tested according to:

UL 1573:2003
 CAN/CSA C22.2 No. 166-M1983
 CAN/CSA C22.2 No. 9-M1989

Production Facility(ies):

13563